

SylProof ToLEDo T8 Twin 1500 IP65 4100Lm 840

Code article 0045885

SYLVANIA


YourHome™




Weatherproof luminaire delivered together with exchangeable ToLEDo T8 LED tubes. Easy to install with stainless steel fixing brackets for ceiling mounting. Polycarbonate housing and diffuser. 4000K; 51W; 4100lm; 80lm/W and 25,000 hours lifetime. IP65; IK08; Class I; 1560mm x 99mm x 78mm

Atouts techniques

Dimensions (mm)



Photométrie



Données générales

Nom du produit	SylProof ToLEDo T8 Twin 1500 IP65 4100Lm 840
Technologie	LED
Cap/Base	G13
Housing	PC Polycarbonate
Montage	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	4100
Luminaire efficacy (lm/W)	80
Colour Code	840
Couleur de lumière	Cool White
IRC (Ra)	80
Maintien du flux à la fin de la durée de vie nominale (lm)	70

SylProof ToLEDo T8 Twin 1500 IP65 4100Lm 840

Code article 0045885

SYLVANIA

Caractéristiques électriques

Lampe incluse	0029298
Consommation électrique totale (W)	51
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	1
Electrical protection	Class I
No. Of switching cycles before premature failures	>200000
Dimmable	No
Dimming method	N/A
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz

Données physiques

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Longueur (mm)	1560
Largeur (mm)	99
Nominal Product Height (mm)	78
Poids (kg)	2.05

Emballage

Product EAN number	5410288458854
Longueur simple de l'emballage (cm)	156.8
Largeur simple de l'emballage (cm)	11.0
Packaging single depth (cm)	8.0
DUN14 (inner)	15410288458851
Units per outer package	72
Packaging outer length / height (cm)	158.5
Packaging outer width (cm)	74.0
Packaging outer depth (cm)	90.0