

SylSplash 1200 IP65 3700lm 840

Code article 0045966

SYLVANIA

Données générales

Nom du produit	SylSplash 1200 IP65 3700lm 840
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montage	Ceiling surface mounting
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Numéro virtuel FI	4278193
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	3700
Luminaire efficacy (lm/W)	103
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	125
Distribution type	Diffuse
Photobiological Risk Group	RG0

Caractéristiques électriques

Consommation électrique totale (W)	36
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	90
Courant d'appel (A)	12
Inrush Duration (µs)	350
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	20
Max. products per 10A B Breaker	10
Max. products per 13A B Breaker	15
Max. products per 16A B Breaker	20
Max. products per 20A B Breaker	25
Connectable conductor cross section - Min (mm ²)	0.5
Connectable conductor cross section - Max (mm ²)	0.5

SylSplash 1200 IP65 3700lm 840

Code article 0045966

SYLVANIA

Durée de vie

Lifespan L70 B50	30000
Lifespan L70 B20	30000
Lifespan L70 B10	30000
Lifespan L80 B50	30000
Lifespan L80 B20	28000
Lifespan L80 B10	24000
Lifespan L90 B50	21000
Lifespan L90 B20	15000
Lifespan L90 B10	13000

Données physiques

Housing colour	White
IP rating	IP65
IK rating	IK04
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Longueur (mm)	1250
Largeur (mm)	53
Nominal Product Height (mm)	35
Poids (kg)	0.3

Emballage

Product EAN number	5410288459660
Longueur simple de l'emballage (cm)	125.3
Largeur simple de l'emballage (cm)	3.7
Packaging single depth (cm)	5.5
DUN14 (inner)	15410288459667
Units per outer package	20
Packaging outer length / height (cm)	128.2
Packaging outer width (cm)	24.5
Packaging outer depth (cm)	21.5

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40