

SYLPROOF TOLEDO T8 L1500 2300LM 865 SINGLE

Code article 0090071

SYLVANIA

YourHome™



Weatherproof luminaire delivered together with exchangeable ToLEDo T8 LED tubes. Easy to install with stainless steel fixing brackets for ceiling mounting. Polycarbonate housing and diffuser. 6500K; 18W; 2300lm; 128lm/W and 25,000 hours lifetime. IP65; IK08; Class II; 1580mm x 60mm x 65mm

Atouts techniques

Photométrie

Données générales

| | |
|----------------------------------|--|
| Nom du produit | SYLPROOF TOLEDO T8 L1500 2300LM 865 SINGLE |
| Technologie | LED |
| Cap/Base | 2G13 |
| Housing | PC Polycarbonate |
| Montage | Wall surface mounted |
| Built in presence detector | NONE |
| General application | Logistics & Industry |
| Operating temperature range (°C) | -20°C...+40°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC002892 |
| Warranty | 3 ans |

Données optiques

| | |
|---------------------------------|-----------|
| Fixture luminous flux (lm) | 2300 |
| Luminaire efficacy (lm/W) | 128 |
| Température de couleur (K) | 6500 |
| Couleur de lumière | Daylight |
| IRC (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Beam Angle (°) | 120 |
| Distribution type | Symmetric |
| Photobiological Risk Group | RG1 |

SYLPROOF TOLEDO T8 L1500 2300LM 865 SINGLE

Code article 0090071

SYLVANIA

Caractéristiques électriques

| | |
|---|--------------|
| Lampe incluse | 0030244 |
| Consommation électrique totale (W) | 18 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.9 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) \leq xx.x % | 20 |
| Electrical protection | Class II |
| Type d'appareillage | Not required |
| Dimmable | No |
| Dimming method | N/A |
| Courant d'appel (A) | 14.9 |
| Inrush Duration (μ s) | 60 |
| Energy Efficiency Class (A->G) of contained light source | D |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 101 |
| Max. products per 16A C Breaker | 161 |
| Max. products per 16A B Breaker | 97 |
| Connectable conductor cross section - Max (mm ²) | 1.5 |

Durée de vie

| | |
|------------------|-------|
| Lifespan L70 B50 | 15000 |
|------------------|-------|

Données physiques

| | |
|-----------------------------|------------------|
| Housing colour | Grey |
| IP rating | IP65 |
| IK rating | IK08 |
| Diffuser finish | Transparent |
| Diffuser material | PC Polycarbonate |
| Longueur (mm) | 1580 |
| Largeur (mm) | 65 |
| Nominal Product Height (mm) | 60 |
| Poids (kg) | 1.0 |

Emballage

| | |
|--------------------------------------|----------------|
| Product EAN number | 5410288900711 |
| Longueur simple de l'emballage (cm) | 160.0 |
| Largeur simple de l'emballage (cm) | 6.6 |
| Packaging single depth (cm) | 6.3 |
| DUN14 (inner) | 15410288900718 |
| Units per outer package | 12 |
| Packaging outer length / height (cm) | 163.0 |
| Packaging outer width (cm) | 21.0 |
| Packaging outer depth (cm) | 30.0 |

Sécurité

| | |
|---|--------|
| Glow Wire Test (°C) | 650 |
| Condition de fonctionnement optimal (° C) | -20-40 |