



# START PANEL IP54 UGR19 TW 600x600 4300LM SSC

Code article 0042706

**SYLVANIA**

## Données générales

Nom du produit	START PANEL IP54 UGR19 TW 600x600 4300LM SSC
Technologie	LED
Cap/Base	N/A
Housing	Steel
Montage	Ceiling recessed mounting
Built in presence detector	NONE
General application	Education, Hospitality, Logistics & Industry, Office
Operating temperature range (°C)	-10°C...+45°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	4320
Luminaire efficacy (lm/W)	114
Colour Code	N/A
Couleur de lumière	Tuneable White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

## Caractéristiques électriques

Consommation électrique totale (W)	38
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15.0
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart SSC
Minimum dimming level (%)	5
Drive current (mA)	900
Courant d'appel (A)	60
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	22
Max. products per 16A C Breaker	35
Max. products per 16A B Breaker	35
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5
<b>Durée de vie</b>	
Lifespan L70 B50	100000
Lifespan L80 B20	61000

# START PANEL IP54 UGR19 TW 600x600 4300LM SSC

Code article 0042706

**SYLVANIA**

## Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP54/20
IK rating	IK03
Diffuser finish	Diffuse
Diffuser material	PS Polystyrene
Longueur (mm)	595
Largeur (mm)	595
Nominal Product Height (mm)	35
Poids (kg)	1.92

## Emballage

Product EAN number	5410288427065
Longueur simple de l'emballage (cm)	60.0
Largeur simple de l'emballage (cm)	3.8
Packaging single depth (cm)	68.5
DUN14 (inner)	15410288427062
Units per outer package	4
Packaging outer length / height (cm)	73.0
Packaging outer width (cm)	17.0
Packaging outer depth (cm)	65.0

## Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-10-45